


JE-H(St)H Bd Si mtp* B2ca/Cca/Dca

acc. to DIN VDE 0815

* capable of maxi-termi-point



Dimension	Sheath thickness approx. mm	Diameter approx. mm	Cable weight approx. kg/km	Copper index kg/km
2 x 2 x 0.8	1.0	6.0	55	25
4 x 2 x 0.8	1.0	7.7	90	45
8 x 2 x 0.8	1.0	10.5	155	85
12 x 2 x 0.8	1.0	11.5	205	126
16 x 2 x 0.8	1.0	12.2	255	166
20 x 2 x 0.8	1.2	14.0	325	206
24 x 2 x 0.8	1.2	14.9	380	246
32 x 2 x 0.8	1.4	18.6	515	327
40 x 2 x 0.8	1.4	20.0	620	407

APPLICATION

This halogen-free, flame-resistant cable is used where increased fire protection of persons, material goods and buildings is required. It serves for signal transmission in communication systems with fixed installation. Not approved for power installation. Due to water absorption the cable should only be laid directly in earth or water if a protective conduit is used.

CONSTRUCTION

- Conductor:** copper, solid, bare (Ø 0.8 mm)
- Core insulation:** halogen-free compound
- Core stranding:** 2 cores to pair, 4 pairs to unit, units in layers; 2 x 2 as star quad
- Lapping:** plastic foil
- Shield:** tinned drain wire (Ø 0.8 mm); plastic-laminated aluminium foil
- Outer sheath:** halogen-free compound; colour: pebble grey RAL 7032 or blue RAL 5015

BEHAVIOUR UNDER FIRE CONDITIONS

- Zero halogen, non corrosive gases: IEC 60754-2, DIN EN 50267
- Flame retardant: IEC 60332-1-2, DIN EN 60332-1-2
- Fire retardant: IEC 60332-3-22, DIN EN 60332-3-22
- Smoke density: IEC 61034, DIN EN 61034

CONSTRUCTION PRODUCTS REGULATIONS

- Dca s1 d2 a1
- Cca s1 d2 a1
- B2ca s1 d1 a1

ELECTRICAL CHARACTERISTICS

(Conductor) loop resistance max.	73.2 Ω/km
Insulation resistance min.	100 MΩ x km
Mutual capacitance (800 Hz) max.	120 nF/km 2 and 4 pair cable plus 20% permitted 1 pair 180nF/km
Capacitance unbalance (800 Hz) max.	200 pF/100m 20% of values, min one value up to 400 pF
Test voltage core-core	500 V 50 Hz 1 min
Test voltage core-screen	2000 V 50 Hz 1 min
Peak operating voltage	225 V

THERMAL & MECHANICAL PROPERTIES

Temperature range during installation	-5°C to +50°C
Temperature range stationary	-30°C to +70°C
Minimum bending radius	7.5 x diameter

Subject to changes due to technical progress and error

